

5 Multisplit Indoors U.Exterior



5AMW125U4RTA

Type(Free Match)		up to 5 indoor units	
EU Model Name		5AMW125U4RTA	
Model Name		AMW5-42U4RTA	
Gas		R32	
Performance			
Capacity	Pdesign Cooling	kW	12.5
	Pdesign Heating	kW	10.5
	Cooling	kW	12.5 3.8 15.3
		Btu/h	42650(12960~52200)
	Heating	kW	13.5 6.7 17.2
Btu/h		46060(22860~58600)	
Air flow		m ³ /h	5000
EER		W/W	3.46
COP		W/W	3.56
SEER			6.50
SCOP			3.72
EEL Rank		Cooling	--
		Heating	--
Noise Level/sound power		dB(A) (Max)	55/61 75
Guaranteed Operating Range	Cooling	°C	-15~48
	Heating	°C	-15~24
Compressor model	Model		KTF400D64UMT
	Brand		GMCC
Electrical Data			
Power		V/Hz/f	220~240/50/1
Power input	Cooling	W	3610 810 7500
	Heating	W	3790(680 7500)
Rated current	Cooling	A	15.6
	Heating	A	16.7
Anti electric shock			Class I
Degrees of protection			IPX4
Dimension & Weight			
Net Dimension (WxHxD)		mm	950x1050x340
Net Weight		kg	90
Package Dimension (WxHxD)		mm	1110x1200x460
Gross Weight		kg	102
Technical Information			
Piping	Diameter(Liquid)	mm	6.35x5
	Diameter(Gas)	mm	9.52x5
	Max Length(Each)	m	20
	Max Length(Total)	m	80
	Max Height	m	15
Upload refrigerant		g	3000
Upload additional refrigerant		g/m	12g/m over 25m

